


CROSSOVER:

P1 568B COLOR	P2 568A COLOR
1 WH/ORG	1 WH/GRN
2 ORG	2 GRN
3 WH/GRN	3 WH/ORG
4 BLU	4 BLU
5 WH/BLU	5 WH/BLU
6 GRN	6 ORG
7 WH/BWN	7 WH/BWN
8 BWN	8 BWN



SHELL ——— DRAIN ——— SHELL

SPECIFICATIONS:

1. CONDUCTOR:

1.1 CONDUCTORS: 26AWG 7*0.16±0.015mm

1.2 CONDUCTOR INSULATION COLOR CODING: ONE WHITE/ORANGE, ONE ORANGE, ONE WHITE/GREEN, ONE BLUE, ONE WHITE/BLUE, ONE GREEN, ONE WHITE/BROWN, ONE BROWN.

2. CABLE JACKET

2.1 PRINTING ON THE JACKET: equip CAT. 5E SF/UTP PATCH CABLE E213738 CM (UL)

C(UL) 4PR 26AWG ISO/IEC 11801 & EN 50288 & TIA/EIA-568-B.2 VERIFIED

3. CABLE ASSEMBLY

3.1 SEE SECTION A-A FOR DIMENSIONS

3.2 CABLE TIE: ACCORDING TO CUSTOMER'S REQUEST

3.3 WIRING CROSSOVER

3.4 CONTACT PLUG: SHIELDED RJ45 8P8C 3u

4. CABLE JACKET COLOR: BLACK

5. LENGTH: L ± 3%mm

REMARK NO	CHAINO	SIGNATURE	DATE	CROSSOVER				
DRAWN BY	MORGAN			SIGN		W.T	SCALE	
CHECKED BY								SF/UTP CAT5E CABLE Lm
AUDITED BY		APPROVED BY						26AWG
CRAFT		DATE	2009. 8. 5	PAGE OF				